



Re-lighting a Stairwell?



FSC Stairwell Light

The 6000 series is a wall or ceiling mount fixture ideal for stairwell lighting and utility applications. A low wattage F17T8 or 10 Watt 2ft LED is constantly on to provide base light levels at all times. Primary lamps are controlled by an occupancy sensor or photocell and shut off during times of inactivity. Fixtures are designed to operate at low temperatures (2' lamp keeps interior area warm).



6000 Series

Replace unsightly fixtures with an attractive alternative. The 6000 series is modern radial wraparound that provides upgraded aesthetics in a cost effective and energy efficient package. The housing is manufactured from cold rolled steel and finished in a white polyester polymer with a clear acrylic lens. The 6000 Series is available in 1, 2 and 3 lamp cross sections with T8, T5 or T5HO lamp configurations.



6000- EB (Extended Body)

The extended fixture housing allows the sensor to be mounted internally within the box or externally depending on customer preference. The inside of the of extended housing can be accessed without tools to allow for simple time delay and photocell adjustment as well as future maintenance should it be needed.

Advanced Lighting Control Options:

FSC can integrate advanced lighting control technology into the fixtures themselves which provide clients with the most energy efficient fixtures available in the marketplace today. Each fixture is individually addressable and can be integrated into the Building Management System. A facility manager can then commission them in the most efficient manner while maintaining safe light levels. Call Factory for more information.



* Occupancy Sensor/ Photocell