



6900 Series

Architectural Indirect Thin Line



General Characteristics:

Lamp Type: 2, 3 or 4 Lamp T5 or T8
 Ballast Type: Electronic Ballast
 Standard Voltage: Universal 120-277
 Options: Dimming Ballast, Emergency Ballast, With Lamps, Dual Cable, Over-Lay Lens, White Louver, Semi- Specular Louver
 Mounting: Suspended with Stems & Cables (*Mounting Hardware is Sold Separately*)
 Additional Info: UL Listed & Title 24 Compliant

Catalog Ordering: Example: 6948-232-UNV

69					
----	--	--	--	--	--

FAMILY TYPE	LENGTH IN INCHES/ LAMPING	# OF BALLAST	BALLAST/ VOLTAGE	OPTIONS
69	48-232 (2- F32T8)	/1	UNV (120-277 Volt)	EMR 800 (800 Lumen Emergency Ballast)
	96-232T (4- F32T8)	/2	DIM (Dimming Ballast)	WL (Lamps Plus)
	48-228 (2- F28T5)			DC (Dual Cable)
	48-328 (3- F28T5)			OL (Overlay Lens)
	48-254 (2- F54T5HO)			LV-W (White Louver)**
	48-354 (3- F54T5HO)			LV- SS (Semi- Specular Louver)**
	96-228T (4- F54T5HO)			
	96-328T (6- F54T5HO)			
	96-254T (4- F54T5HO)			
	96-354T (6- F54T5HO)			

** Not available in T8 configurations

Specifications and Dimensions Subject to change without notice
 FSC Lighting 9120 Center Avenue, Rancho Cucamonga, CA 91730 Ph 909-948-8878 Fax 909-948-8510



Revised 1/17/14

Catalog No.	Type:
Job Name:	

Features & Specifications:

The 6900 Series is an architectural indirect thin line ideal for open office ambient lighting for virtually glare free and shadow free illumination. Designed with an optical system that maximizes the output of the lamps producing very wide distribution for even ceiling brightness with mounting from 12- 18 inches from the ceiling.

- Housing made of 20 gauge cold rolled steel
- Standard in perforated white powder coat housing (over-layer lens, semi- specular or white louver also available)
- Enhanced anodized aluminum reflector
- Reflectors are slotted when used with the perforated housing
- Available in a variety of lamp configurations
- Die cast aluminum ends
- Dual Cable Kit available optional (*Mounting Hardware is Sold Separately*)
- Suitable for damp location

