



# New Versions! L6000 Series- Radial Wrap



## Highlights:

- Highest lumens per watt in category
- Highest AMBIENT temperature rating in the category (50°C / 122°F)
- Flexible connectors secure PCB to heat sink ensures consistent contact and thermal management

## Applications Include:

- Parking Garages
- Stairwells
- Distribution Centers
- Laundry Rooms
- Covered Parking
- Corridors
- Canopies
- Back of House

## Features:

- Low first cost (lowest cost per lumen in category)
- Capable of Handling Any Lighting Control Strategy
- Occupancy Sensor - Turn Off Fixture
- Photo Cell - Turn Fixture Off from Ambient Light
- Step Dim - Turn lights to low level
- Dim - Full range dimming
- Remote Control Programmers
- Available Auto Demand Response (ADR) Ready
- DLC & Lighting Facts
- Exceeds New DLC Premium Standards

## Technical Information:

- Light Source: LED PCB with Flexible Clips
- Power Source: LED High Efficiency Power Supply
- Voltage: Universal 120 to 277
- CCT (Kelvin Temp): 30K, 35K, 40K & 50K
- Mounting: Surface, Ceiling, Wall (brackets and boxes available)
- CRI: 80+
- Driver is 0-10V dimming STANDARD
- Power Factor: >.95

## Lumen Packages:

### Low Lumen Package:

2' Fixture	16.5 watts	2000 lumens
4' Fixture	31.5 watts	4100 lumens

### High Lumen Package:

2' Fixture	27.5 watts	2600 lumens
4' Fixture	51.5 watts	5800 lumens

