


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz Lamp Flux:3530.05x1 lm		
NAME: L7414-30W-AOK-RFKW-SL		
MFR.: EVERFINE		

DATA OF LAMP		PHOTOMETRIC DATA Eff: 141.56 lm/W			
MODEL		I _{max} (cd)	1358	S/MH (C0/180)	1.24
NOMINAL POWER(W)	25	LOR(%)	100.0	S/MH (C90/270)	1.26
RATED VOLTAGE(V)	120	TOTAL FLUX (lm)	3530.0	η UP,DN (C0-180)	0.0,50.2
NOMINAL FLUX(lm)	3530.05	CIE CLASS	DIRECT	η UP,DN (C180-360)	0.0,49.8
LAMPS INSIDE	1	η up (%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE (V)	120	η down (%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H(β) Range: -90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2024-08-09

V(B) Range: -90 - 90DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity: 65.0%
Test Distance: 6.300m [K=0.9841]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1331	1318	1316	1314	1337	1311	1312	1315	0- 10	127.3	127.3	3.6,3.6
20	1251	1259	1274	1241	1263	1236	1266	1252	10- 20	363.9	491.1	13.9,13.9
30	1105	1154	1157	1144	1133	1138	1152	1144	20- 30	553.5	1045	29.6,29.6
40	883.5	972.5	1015	975.2	932.8	973.9	1014	959.1	30- 40	659.4	1704	48.3,48.3
50	598.3	763.9	810.8	774.9	662.5	778.2	806.6	747.6	40- 50	664.1	2368	67.1,67.1
60	340.4	523.6	543.9	530.9	393.5	533.4	529.0	507.2	50- 60	548.5	2917	82.6,82.6
70	166.7	286.9	305.7	280.8	205.6	280.8	285.2	271.8	60- 70	362.3	3279	92.9,92.9
80	43.69	126.5	153.5	118.0	75.49	117.6	143.1	117.5	70- 80	191.3	3470	98.3,98.3
90	0.3995	1.129	1.266	1.260	1.096	0.9374	0.9549	0.8556	80- 90	59.77	3530	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 2.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2024-08-09

$V(B)$ Range:-90 - 90DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
 Humidity:65.0%
 Test Distance:6.300m [K=0.9841]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz		
Lamp Flux:3530.05x1 lm		
NAME: L7414-30W-AOK-REKW-SL		
MFR.: EVERFINE		



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	116	1364
80	387	1360
75	595	1362
70	750	1375
65	893	1492
60	1047	1674
55	1232	1814
50	1432	1941
45	1620	2052

H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2024-08-09

V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:

V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:

WEC AND CCEC

Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz											
Lamp Flux:3530.05x1 lm											
NAME: L7414-30W-AOK-REKW-SL											
MFR.: EVERFINE											

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)									
0.0																
1.0	.293	.167	.053	.286	.163	.052	.273	.157	.050	.261	.151	.048	.250	.145	.047	
2.0	.278	.152	.047	.271	.149	.046	.260	.144	.045	.249	.140	.044	.239	.135	.043	
3.0	.258	.138	.041	.253	.136	.041	.243	.132	.040	.233	.128	.039	.225	.124	.038	
4.0	.240	.125	.037	.235	.123	.036	.226	.120	.036	.218	.117	.035	.210	.114	.035	
5.0	.223	.114	.033	.219	.112	.033	.211	.110	.032	.203	.107	.032	.196	.105	.031	
6.0	.207	.104	.030	.204	.103	.030	.197	.101	.029	.190	.099	.029	.184	.097	.029	
7.0	.194	.096	.027	.190	.095	.027	.184	.093	.027	.178	.091	.027	.172	.090	.026	
8.0	.181	.089	.025	.178	.088	.025	.173	.086	.025	.167	.085	.024	.162	.083	.024	
9.0	.170	.082	.023	.168	.082	.023	.163	.080	.023	.158	.079	.023	.153	.078	.022	
10.0	.161	.077	.021	.158	.076	.021	.154	.075	.021	.149	.074	.021	.145	.073	.021	

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients(CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.179	.156	.136	.153	.134	.117	.105	.092	.081	.060	.053	.047	.019	.017	.015	
2.0	.170	.132	.100	.146	.114	.086	.100	.079	.060	.058	.046	.035	.018	.015	.011	
3.0	.162	.114	.076	.139	.099	.066	.096	.068	.046	.055	.040	.027	.018	.013	.009	
4.0	.155	.101	.060	.133	.087	.052	.091	.061	.037	.053	.036	.022	.017	.012	.007	
5.0	.147	.090	.048	.126	.078	.042	.087	.055	.030	.050	.032	.018	.016	.010	.006	
6.0	.140	.082	.040	.120	.071	.035	.083	.050	.025	.048	.029	.015	.016	.010	.005	
7.0	.134	.075	.034	.115	.065	.030	.079	.046	.021	.046	.027	.012	.015	.009	.004	
8.0	.127	.069	.029	.110	.060	.025	.076	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.121	.064	.026	.105	.056	.022	.072	.039	.016	.042	.023	.009	.014	.008	.003	
10.0	.116	.060	.023	.100	.052	.020	.069	.037	.014	.040	.022	.008	.013	.007	.003	

H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2024-08-09

V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz										
Lamp Flux:3530.05x1 lm										
NAME: L7414-30W-AOK-REKW-SL										
MFR.: EVERFINE										
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	9.2	10.6	9.4	10.8	11.0	10.7	12.2	11.0	12.4	12.6
3H	9.9	11.3	10.2	11.5	11.8	11.9	13.3	12.2	13.5	13.7
4H	10.2	11.5	10.5	11.7	12.0	12.5	13.7	12.8	14.0	14.2
6H	10.3	11.5	10.6	11.8	12.0	12.9	14.1	13.3	14.4	14.7
8H	10.3	11.5	10.6	11.7	12.0	13.1	14.3	13.5	14.6	14.9
12H	10.2	11.4	10.6	11.7	12.0	13.3	14.4	13.6	14.7	15.0
4H 2H	10.0	11.3	10.3	11.5	11.8	11.2	12.4	11.5	12.7	12.9
3H	10.9	12.1	11.3	12.4	12.7	12.5	13.7	12.9	14.0	14.3
4H	11.3	12.3	11.7	12.6	13.0	13.2	14.3	13.6	14.6	14.9
6H	11.5	12.4	11.9	12.8	13.1	13.9	14.8	14.3	15.1	15.5
8H	11.5	12.4	11.9	12.7	13.1	14.1	15.0	14.5	15.3	15.7
12H	11.5	12.3	11.9	12.7	13.1	14.3	15.1	14.8	15.5	15.9
8H 4H	11.7	12.5	12.1	12.9	13.3	13.4	14.2	13.8	14.6	15.0
6H	12.0	12.7	12.5	13.1	13.6	14.2	14.9	14.6	15.3	15.7
8H	12.1	12.7	12.6	13.2	13.6	14.6	15.2	15.0	15.6	16.1
12H	12.2	12.7	12.6	13.1	13.6	14.9	15.4	15.4	15.9	16.3
12H 4H	11.7	12.5	12.1	12.9	13.3	13.4	14.2	13.8	14.5	14.9
6H	12.2	12.8	12.6	13.2	13.6	14.2	14.8	14.7	15.3	15.7
8H	12.3	12.8	12.8	13.3	13.8	14.6	15.2	15.1	15.6	16.1
Variations with the observer position at spacings(CIE Pub.117):										
S = 1.0H	+ 0.4 / - 0.4					+ 0.2 / - 0.2				
1.5H	+ 0.3 / - 0.5					+ 0.2 / - 0.4				
2.0H	+ 0.4 / - 1.0					+ 0.2 / - 0.3				

CIE Pub.117, 3530 lm Total Lamp Luminous Flux Correct (8log(F/F0) = 4.4)
Area: 0.65 m2

H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2024-08-09

V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz		
Lamp Flux:3530.05x1 lm		
NAME: L7414-30W-AOK-REKW-SL		
MFR.: EVERFINE		


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	59	48	41	59	48	41	58	47	41	35
0.80	70	58	51	69	58	51	67	57	51	44
1.00	78	67	60	77	67	60	75	68	60	53
1.25	85	75	68	84	74	68	81	73	67	60
1.50	90	81	74	88	80	73	85	78	72	65
2.00	97	88	82	95	87	82	91	85	80	73
2.50	100	93	87	98	91	86	94	89	84	76
3.00	103	97	92	101	95	91	97	92	88	80
4.00	107	102	97	105	100	96	101	97	93	85
5.00	109	105	101	107	103	99	102	99	96	87
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 2.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:DAMIN
 Test Date:2024-08-09

$V(B)$ Range:-90 - 90DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
 Humidity:65.0%
 Test Distance:6.300m [K=0.9841]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz		
Lamp Flux:3530.05x1 lm		
NAME: L7414-30W-AOK-RFKW-SL		
MFR.: EVERFINE		




H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2024-08-09

V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:

AAI Figure

Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz Lamp Flux:3530.05x1 lm		
NAME: L7414-30W-AOK-REKW-SL		
MFR.: EVERFINE		




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range: -90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature: 25.3DEG
Operators: DAMIN
Test Date: 2024-08-09

V(B) Range: -90 - 90DEG
V(B) Interval: 5.0DEG
Test System: EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity: 65.0%
Test Distance: 6.300m [K=0.9841]
Remarks:

ISOLUX DIAGRAM

Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz Lamp Flux:3530.05x1 lm		
NAME: L7414-30W-AOK-RFKW-SL		
MFR.: EVERFINE		



H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2024-08-09

V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:

LED Avg.L Report

Test:U:120.39V I:0.2075A P:24.937W PF:0.9981 Freq:59.98Hz Lamp Flux:3530.05x1 lm		
NAME: L7414-30W-AOK-REKW-SL		
MFR.: EVERFINE		


AvgL	cd/m2
L_0~180 (65) av	973
L_0~180 (75) av	702
L_0~180 (85) av	291
L_90~270 (65) av	1456
L_90~270 (75) av	1318
L_90~270 (85) av	1318
L_45 (65) av	1446
L_45 (75) av	1101
L_45 (85) av	1054

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2024-08-09

V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 2.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:DAMIN
Test Date:2024-08-09

V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:

```
V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:
```

```
V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:
```

```
V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:
```

```
V(B) Range:-90 - 90DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.446
Humidity:65.0%
Test Distance:6.300m [K=0.9841]
Remarks:
```