

Report No.:

Test Time: 2025/1/21 15:39

Luminaire Property

Luminaire Manufacturer:

Luminaire Category:

Lamp Catalog:

Number of Lamps:

Luminous Length (mm):

Luminous Height (mm):

Current: 1.265 A

Power Factor: 0.999

Luminaire Description:

Lamp Description:

Lumens per Lamp:

Luminous Width (mm):

Voltage: 120.0 V

Power: 151.61 W

Photometric Results

IES Classification: Type I

Total Rated Lamp Lumens: 20242.5 lm

Efficiency: 100%

Upward Ratio: 0%

C0r0 Intensity: 11351.04 cd

Pos of Max. Intensity: H0 V6

Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 91.4, 73.3, 82.5, 81.8

Longitudinal Classification: Very Short


Measurement Flux: 20242.5 lm

Downward Ratio: 100%


Luminaire Efficacy Rating (LER): 133.57

Max. Intensity: 11401.66 cd

Picture Of Luminaire



Luminous Intensity Distribution Curve



Unit: cd

Average Diffuse Angle(50%): 82.4°

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 22.5

Test Lab:

Test Type: TYPE C

Temperature: 24.6 'C

Operator:

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-3000

Distance: 14.631 m [K=1.0000]

Humidity:

Inspector:


Photon Intensity Distribution Curve



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1	1.11	1.08	1.05	1.02	1.09	1.06	1.03	1.00	1.01	0.99	0.97	0.98	0.96	0.94	0.94	0.93	0.91	0.89
2	1.04	0.97	0.92	0.87	1.01	0.95	0.90	0.86	0.92	0.88	0.84	0.89	0.85	0.82	0.86	0.83	0.81	0.79
3	0.96	0.88	0.81	0.76	0.94	0.86	0.80	0.75	0.83	0.78	0.74	0.81	0.76	0.73	0.78	0.75	0.71	0.70
4	0.89	0.79	0.72	0.67	0.87	0.78	0.71	0.66	0.76	0.70	0.65	0.74	0.69	0.64	0.72	0.67	0.64	0.62
5	0.83	0.72	0.65	0.59	0.81	0.71	0.64	0.59	0.69	0.63	0.58	0.67	0.62	0.58	0.66	0.61	0.57	0.55
6	0.78	0.66	0.58	0.53	0.76	0.65	0.58	0.53	0.64	0.57	0.52	0.62	0.56	0.52	0.60	0.55	0.51	0.50
7	0.73	0.61	0.53	0.48	0.71	0.60	0.53	0.48	0.59	0.52	0.47	0.57	0.51	0.47	0.56	0.51	0.47	0.45
8	0.68	0.56	0.48	0.43	0.67	0.55	0.48	0.43	0.54	0.48	0.43	0.53	0.47	0.43	0.52	0.47	0.43	0.41
9	0.64	0.52	0.45	0.40	0.63	0.51	0.44	0.39	0.50	0.44	0.39	0.49	0.43	0.39	0.48	0.43	0.39	0.37
10	0.60	0.48	0.41	0.36	0.59	0.48	0.41	0.36	0.47	0.40	0.36	0.46	0.40	0.36	0.45	0.40	0.36	0.34

Spacing Criteria (0-180): 1.23

Spacing Criteria (90-270): 1.08

Spacing Criteria (Diagonal): 1.17



C Plane (°):0.0-360.0: 22.5

Test Lab:

Test Type: TYPE C

Temperature: 24.6 'C

Operator:

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-3000

Distance: 14.631 m [K=1.0000]

Humidity:

Inspector:


Isocandela (rectangle)



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Isocandela (sphere)



Imax (100%): 11402 cd

(10%): 1140 cd
(25%): 2850 cd
(63%): 7183 cd

(16%): 1824 cd
(40%): 4561 cd
(100%): 11402 cd


CIE: narrow - short
CIE: Full-cut-off luminaire
Max.At90: 0.000 cd/klm

IES: Cut-off
Max.At80: 0.000 cd/klm
Max.80-90: 0.000 cd/klm

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

IsoLux Plot




Mounting Height: 10.0m		Max Lux(100%): 113.6 lx	
— (1%):	1.1 lx	— (2%):	2.3 lx
— (3%):	3.4 lx	— (4%):	4.5 lx
— (5%):	5.7 lx	— (6%):	6.8 lx
— (7%):	8.0 lx	— (8%):	9.1 lx
— (9%):	10.2 lx	— (10%):	11.4 lx

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Roadway CU Curve

Efficiency(%)





C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h




L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	5217	3952	2874	1908	1336	936	620	312	49
C90	3364	2415	1809	1315	814	442	181	35	20
C180	6871	5015	3482	2274	1456	852	433	157	20
C270	3254	2268	1669	1190	775	467	254	106	36

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:


Illuminance at a Distance



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 10.0m Max Lux: 11351.0 lx

(1%): 113.5 lx	(2%): 227.0 lx
(3%): 340.5 lx	(4%): 454.0 lx
(5%): 567.6 lx	(6%): 681.1 lx
(7%): 794.6 lx	(8%): 908.1 lx
(9%): 1021.6 lx	(10%): 1135.1 lx

C Plane (°): 0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°): 0.0-180.0: 1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Area Flux Table

Unit: lm


Vertical plane		-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90
		0.0	0.1	0.2	0.3	0.5	0.7	0.9	1.1	1.2	1.3	1.2	1.0	0.8	0.5	0.4	0.2	0.1	0.0	0.0
		0.0	0.1	0.5	1.3	2.6	4.4	6.2	7.5	8.0	8.2	8.0	6.8	4.9	3.0	1.7	0.7	0.2	0.0	64.4
		0.0	0.3	1.6	4.7	9.0	14.3	19.0	22.4	24.2	24.8	24.1	20.7	15.0	9.4	5.2	2.2	0.6	0.1	197.4
		0.0	0.7	3.9	10.8	20.8	31.5	41.0	47.3	51.2	51.5	48.3	41.2	31.1	20.1	10.7	4.5	1.3	0.1	416.1
		0.1	1.4	7.0	19.9	38.6	59.2	79.5	92.3	100.9	100.3	90.5	73.4	52.8	34.0	17.8	7.5	2.2	0.1	777.7
		0.1	2.1	10.7	31.4	64.7	106.4	147.0	172.6	189.2	189.0	168.6	131.9	88.1	52.6	26.1	10.6	3.1	0.2	1394.4
		0.1	2.9	14.3	43.2	98.1	165.2	219.0	252.4	272.8	275.1	250.2	200.0	133.9	75.4	35.3	13.5	3.9	0.3	2055.0
		0.1	3.5	17.3	53.7	126.0	209.0	264.2	295.4	317.8	322.2	297.5	245.9	171.4	96.3	43.7	15.8	4.5	0.3	2484.2
		0.2	3.8	19.2	60.8	142.6	226.5	280.9	313.5	336.5	341.5	318.4	267.3	190.6	109.6	49.6	17.4	5.0	0.4	2683.2
		0.2	3.9	19.1	60.4	141.7	225.1	279.4	312.8	336.8	342.2	318.9	268.0	191.3	110.4	50.1	17.6	5.0	0.4	2683.2
		0.1	3.5	17.3	52.8	123.4	205.1	260.9	294.7	318.3	322.6	298.3	247.4	173.5	98.7	45.0	16.3	4.6	0.3	2483.0
		0.1	2.9	14.4	42.0	94.7	161.6	216.1	251.0	271.6	273.0	249.2	202.0	138.0	79.3	37.3	14.1	4.0	0.3	2051.2
		0.1	2.2	10.9	30.6	62.6	104.1	146.0	173.1	189.5	189.4	171.2	137.3	93.9	56.7	28.3	11.3	3.2	0.2	1410.0
		0.1	1.4	7.4	20.1	38.2	58.8	80.3	94.9	104.1	104.4	95.8	79.3	58.1	37.7	19.8	8.2	2.3	0.1	810.9
		0.0	0.8	4.2	11.1	21.2	32.4	43.0	50.6	55.2	56.1	53.2	46.0	35.3	22.9	12.0	5.0	1.4	0.1	450.5
		0.0	0.3	1.7	4.7	8.9	14.2	19.1	23.2	25.4	26.4	26.0	22.4	16.4	10.2	5.6	2.3	0.6	0.1	207.3
		0.0	0.1	0.4	1.1	2.0	3.3	4.6	5.7	6.2	6.5	6.5	5.6	4.2	2.7	1.6	0.7	0.2	0.0	51.5
		0.0	0.1	0.2	0.3	0.4	0.5	0.5	0.6	0.6	0.6	0.6	0.6	0.5	0.4	0.3	0.2	0.1	0.0	6.8
		1.4	30.3	150.3	449.0	996.0	1622.2	2107.2	2411.3	2609.2	2635.2	2426.6	1996.8	1399.8	820.0	390.4	148.2	42.2	3.1	20240
		0.0	0.0	78.7	396.3	944.2	1567.2	2051.2	2353.2	2553.0	2578.2	2369.8	1941.0	1345.0	764.3	3328.7	65.4	0.0	0.0	19338

Horizontal plane

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:


The Average Illuminance Effective Figure



C Plane (°): 0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM




ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	10157	50.2
FL (0°-30°)	4252	21.0
FM (30°-60°)	5162	25.5
FH (60°-80°)	724	3.6
FVH (80°-90°)	19	0.1
BACK LIGHT	10086	49.8
BL (0°-30°)	4256	21.0
BM (30°-60°)	5102	25.2
BH (60°-80°)	703	3.5
BVH (80°-90°)	24	0.1
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-11	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B4 U0 G2
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B4 U0 G1

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 24.6 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

LCS Graph



Back Light

Forward Light

Scale= MAX LCS%

Trapped Light:NA,NA

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 1.00									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.67	0.77	0.84	0.88	0.95	0.99	1.01	1.05	1.07	
	0.30		0.61	0.71	0.78	0.83	0.90	0.94	0.98	1.02	1.05	
	0.20		0.56	0.66	0.73	0.79	0.86	0.91	0.94	0.99	1.02	
0.50	0.50	0.20	0.66	0.75	0.82	0.86	0.92	0.95	0.98	1.01	1.03	
	0.30		0.60	0.70	0.76	0.81	0.88	0.92	0.95	0.99	1.01	
	0.20		0.56	0.66	0.72	0.77	0.84	0.89	0.92	0.96	0.99	
0.30	0.50	0.20	0.65	0.74	0.80	0.84	0.89	0.92	0.95	0.98	0.99	
	0.30		0.59	0.69	0.75	0.80	0.86	0.89	0.92	0.95	0.98	
	0.20		0.55	0.65	0.72	0.76	0.83	0.87	0.90	0.94	0.96	
0.00	0.00	0.00	0.53	0.63	0.69	0.73	0.79	0.83	0.86	0.89	0.91	
Rating:152W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 1.00									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.84	0.67	0.56	0.48	0.38	0.31	0.26	0.20	0.16	
	0.30		0.70	0.57	0.49	0.43	0.34	0.28	0.24	0.19	0.15	
	0.20		0.60	0.50	0.43	0.38	0.31	0.26	0.23	0.18	0.15	
0.50	0.50	0.20	0.81	0.64	0.53	0.46	0.36	0.33	0.25	0.19	0.15	
	0.30		0.68	0.56	0.47	0.41	0.33	0.27	0.23	0.18	0.15	
	0.20		0.59	0.49	0.42	0.37	0.30	0.25	0.22	0.17	0.14	
0.30	0.50	0.20	0.78	0.61	0.51	0.44	0.34	0.27	0.23	0.18	0.14	
	0.30		0.67	0.54	0.46	0.40	0.31	0.26	0.22	0.17	0.14	
	0.20		0.58	0.48	0.41	0.36	0.29	0.24	0.21	0.16	0.13	
0.00	0.00	0.00	0.47	0.37	0.31	0.27	0.21	0.17	0.14	0.11	0.09	
Rating:152W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 1.00									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.15	0.16	0.17	0.18	0.19	0.20	0.20	0.21	0.21	
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.19	0.19	
	0.20		0.05	0.07	0.09	0.10	0.12	0.14	0.15	0.16	0.18	
0.50	0.50	0.20	0.14	0.16	0.17	0.17	0.18	0.19	0.19	0.20	0.20	
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.18	0.19	
	0.20		0.05	0.07	0.08	0.10	0.12	0.13	0.14	0.16	0.17	
0.30	0.50	0.20	0.14	0.15	0.16	0.17	0.17	0.18	0.19	0.19	0.19	
	0.30		0.09	0.10	0.12	0.13	0.14	0.15	0.16	0.17	0.18	
	0.20		0.05	0.07	0.08	0.10	0.11	0.13	0.14	0.15	0.16	
0.00	0.00	0.00	NA	NA	NA	NA	NA	NA	NA	NA	NA	
Rating:152W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	11349.6	10.9	10.9	0.05	0.05
1.0-2.0	11345.7	32.6	43.4	0.16	0.21
2.0-3.0	11338.6	54.2	97.7	0.27	0.48
3.0-4.0	11326.0	75.8	173.5	0.37	0.86
4.0-5.0	11308.3	97.3	270.8	0.48	1.34
5.0-6.0	11286.0	118.6	389.4	0.59	1.92
6.0-7.0	11257.7	139.8	529.2	0.69	2.61
7.0-8.0	11223.3	160.6	689.8	0.79	3.41
8.0-9.0	11182.9	181.3	871.1	0.90	4.30
9.0-10.0	11136.5	201.6	1072.6	1.00	5.30
10.0-11.0	11084.3	221.5	1294.1	1.09	6.39
11.0-12.0	11025.4	241.0	1535.2	1.19	7.58
12.0-13.0	10960.5	260.1	1795.3	1.29	8.87
13.0-14.0	10889.4	278.8	2074.1	1.38	10.25
14.0-15.0	10811.9	296.9	2371.0	1.47	11.71
15.0-16.0	10729.6	314.4	2685.4	1.55	13.27
16.0-17.0	10640.1	331.4	3016.8	1.64	14.90
17.0-18.0	10543.3	347.7	3364.5	1.72	16.62
18.0-19.0	10440.9	363.3	3727.8	1.79	18.42
19.0-20.0	10331.4	378.2	4105.9	1.87	20.28
20.0-21.0	10215.5	392.3	4498.3	1.94	22.22
21.0-22.0	10090.8	405.6	4903.8	2.00	24.23
22.0-23.0	9961.3	418.0	5321.9	2.07	26.29
23.0-24.0	9823.7	429.6	5751.4	2.12	28.41
24.0-25.0	9678.2	440.1	6191.5	2.17	30.59
25.0-26.0	9524.5	449.7	6641.2	2.22	32.81
26.0-27.0	9357.7	457.9	7099.1	2.26	35.07
27.0-28.0	9179.9	464.8	7563.9	2.30	37.37
28.0-29.0	8987.4	470.3	8034.2	2.32	39.69
29.0-30.0	8786.0	474.4	8508.6	2.34	42.03
30.0-31.0	8576.6	477.3	8986.0	2.36	44.39
31.0-32.0	8350.4	478.5	9464.4	2.36	46.76
32.0-33.0	8108.6	477.8	9942.2	2.36	49.12
33.0-34.0	7855.8	475.5	10417.7	2.35	51.46
34.0-35.0	7589.3	471.4	10889.1	2.33	53.79
35.0-36.0	7313.8	465.7	11354.8	2.30	56.09

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	7031.9	458.7	11813.5	2.27	58.36
37.0-38.0	6743.0	450.1	12263.6	2.22	60.58
38.0-39.0	6449.9	440.3	12703.9	2.18	62.76
39.0-40.0	6154.4	429.3	13133.2	2.12	64.88
40.0-41.0	5858.9	417.3	13550.5	2.06	66.94
41.0-42.0	5564.9	404.4	13954.8	2.00	68.94
42.0-43.0	5271.8	390.6	14345.4	1.93	70.87
43.0-44.0	4982.2	376.1	14721.5	1.86	72.73
44.0-45.0	4697.4	361.1	15082.5	1.78	74.51
45.0-46.0	4418.6	345.6	15428.2	1.71	76.22
46.0-47.0	4152.5	330.3	15758.5	1.63	77.85
47.0-48.0	3894.2	314.8	16073.3	1.56	79.40
48.0-49.0	3641.5	299.1	16372.4	1.48	80.88
49.0-50.0	3401.9	283.7	16656.1	1.40	82.28
50.0-51.0	3178.4	268.9	16925.0	1.33	83.61
51.0-52.0	2970.2	254.9	17179.9	1.26	84.87
52.0-53.0	2775.0	241.4	17421.3	1.19	86.06
53.0-54.0	2591.1	228.4	17649.7	1.13	87.19
54.0-55.0	2417.5	215.8	17865.6	1.07	88.26
55.0-56.0	2255.3	203.8	18069.4	1.01	89.26
56.0-57.0	2103.5	192.4	18261.8	0.95	90.22
57.0-58.0	1959.1	181.2	18442.9	0.90	91.11
58.0-59.0	1820.6	170.2	18613.2	0.84	91.95
59.0-60.0	1687.8	159.5	18772.6	0.79	92.74
60.0-61.0	1560.2	148.9	18921.6	0.74	93.47
61.0-62.0	1440.3	138.8	19060.4	0.69	94.16
62.0-63.0	1328.4	129.2	19189.6	0.64	94.80
63.0-64.0	1221.3	119.9	19309.4	0.59	95.39
64.0-65.0	1119.7	110.8	19420.3	0.55	95.94
65.0-66.0	1022.0	102.0	19522.2	0.50	96.44
66.0-67.0	927.4	93.3	19615.5	0.46	96.90
67.0-68.0	835.8	84.7	19700.2	0.42	97.32
68.0-69.0	747.7	76.3	19776.5	0.38	97.70
69.0-70.0	668.3	68.6	19845.1	0.34	98.04
70.0-71.0	594.9	61.5	19906.6	0.30	98.34
71.0-72.0	526.1	54.7	19961.3	0.27	98.61

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	462.9	48.4	20009.7	0.24	98.85
73.0-74.0	402.2	42.3	20052.0	0.21	99.06
74.0-75.0	345.2	36.5	20088.5	0.18	99.24
75.0-76.0	294.4	31.3	20119.8	0.15	99.39
76.0-77.0	248.4	26.5	20146.2	0.13	99.52
77.0-78.0	205.3	22.0	20168.2	0.11	99.63
78.0-79.0	165.3	17.8	20186.0	0.09	99.72
79.0-80.0	129.9	14.0	20200.0	0.07	99.79
80.0-81.0	100.8	10.9	20210.9	0.05	99.84
81.0-82.0	76.0	8.2	20219.1	0.04	99.88
82.0-83.0	54.7	5.9	20225.1	0.03	99.91
83.0-84.0	39.5	4.3	20229.4	0.02	99.94
84.0-85.0	30.3	3.3	20232.7	0.02	99.95
85.0-86.0	23.7	2.6	20235.3	0.01	99.96
86.0-87.0	19.9	2.2	20237.5	0.01	99.98
87.0-88.0	18.8	2.1	20239.5	0.01	99.99
88.0-89.0	17.9	2.0	20241.5	0.01	100.00
89.0-90.0	8.8	1.0	20242.5	0.00	100.00
90.0-91.0	0.0	0.0	20242.5	0.00	100.00
91.0-92.0	0.0	0.0	20242.5	0.00	100.00
92.0-93.0	0.0	0.0	20242.5	0.00	100.00
93.0-94.0	0.0	0.0	20242.5	0.00	100.00
94.0-95.0	0.0	0.0	20242.5	0.00	100.00
95.0-96.0	0.0	0.0	20242.5	0.00	100.00
96.0-97.0	0.0	0.0	20242.5	0.00	100.00
97.0-98.0	0.0	0.0	20242.5	0.00	100.00
98.0-99.0	0.0	0.0	20242.5	0.00	100.00
99.0-100.0	0.0	0.0	20242.5	0.00	100.00
100.0-101.0	0.0	0.0	20242.5	0.00	100.00
101.0-102.0	0.0	0.0	20242.5	0.00	100.00
102.0-103.0	0.0	0.0	20242.5	0.00	100.00
103.0-104.0	0.0	0.0	20242.5	0.00	100.00
104.0-105.0	0.0	0.0	20242.5	0.00	100.00
105.0-106.0	0.0	0.0	20242.5	0.00	100.00
106.0-107.0	0.0	0.0	20242.5	0.00	100.00
107.0-108.0	0.0	0.0	20242.5	0.00	100.00

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 3)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	0.0	0.0	20242.5	0.00	100.00
109.0-110.0	0.0	0.0	20242.5	0.00	100.00
110.0-111.0	0.0	0.0	20242.5	0.00	100.00
111.0-112.0	0.0	0.0	20242.5	0.00	100.00
112.0-113.0	0.0	0.0	20242.5	0.00	100.00
113.0-114.0	0.0	0.0	20242.5	0.00	100.00
114.0-115.0	0.0	0.0	20242.5	0.00	100.00
115.0-116.0	0.0	0.0	20242.5	0.00	100.00
116.0-117.0	0.0	0.0	20242.5	0.00	100.00
117.0-118.0	0.0	0.0	20242.5	0.00	100.00
118.0-119.0	0.0	0.0	20242.5	0.00	100.00
119.0-120.0	0.0	0.0	20242.5	0.00	100.00
120.0-121.0	0.0	0.0	20242.5	0.00	100.00
121.0-122.0	0.0	0.0	20242.5	0.00	100.00
122.0-123.0	0.0	0.0	20242.5	0.00	100.00
123.0-124.0	0.0	0.0	20242.5	0.00	100.00
124.0-125.0	0.0	0.0	20242.5	0.00	100.00
125.0-126.0	0.0	0.0	20242.5	0.00	100.00
126.0-127.0	0.0	0.0	20242.5	0.00	100.00
127.0-128.0	0.0	0.0	20242.5	0.00	100.00
128.0-129.0	0.0	0.0	20242.5	0.00	100.00
129.0-130.0	0.0	0.0	20242.5	0.00	100.00
130.0-131.0	0.0	0.0	20242.5	0.00	100.00
131.0-132.0	0.0	0.0	20242.5	0.00	100.00
132.0-133.0	0.0	0.0	20242.5	0.00	100.00
133.0-134.0	0.0	0.0	20242.5	0.00	100.00
134.0-135.0	0.0	0.0	20242.5	0.00	100.00
135.0-136.0	0.0	0.0	20242.5	0.00	100.00
136.0-137.0	0.0	0.0	20242.5	0.00	100.00
137.0-138.0	0.0	0.0	20242.5	0.00	100.00
138.0-139.0	0.0	0.0	20242.5	0.00	100.00
139.0-140.0	0.0	0.0	20242.5	0.00	100.00
140.0-141.0	0.0	0.0	20242.5	0.00	100.00
141.0-142.0	0.0	0.0	20242.5	0.00	100.00
142.0-143.0	0.0	0.0	20242.5	0.00	100.00
143.0-144.0	0.0	0.0	20242.5	0.00	100.00

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 4)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	0.0	0.0	20242.5	0.00	100.00
145.0-146.0	0.0	0.0	20242.5	0.00	100.00
146.0-147.0	0.0	0.0	20242.5	0.00	100.00
147.0-148.0	0.0	0.0	20242.5	0.00	100.00
148.0-149.0	0.0	0.0	20242.5	0.00	100.00
149.0-150.0	0.0	0.0	20242.5	0.00	100.00
150.0-151.0	0.0	0.0	20242.5	0.00	100.00
151.0-152.0	0.0	0.0	20242.5	0.00	100.00
152.0-153.0	0.0	0.0	20242.5	0.00	100.00
153.0-154.0	0.0	0.0	20242.5	0.00	100.00
154.0-155.0	0.0	0.0	20242.5	0.00	100.00
155.0-156.0	0.0	0.0	20242.5	0.00	100.00
156.0-157.0	0.0	0.0	20242.5	0.00	100.00
157.0-158.0	0.0	0.0	20242.5	0.00	100.00
158.0-159.0	0.0	0.0	20242.5	0.00	100.00
159.0-160.0	0.0	0.0	20242.5	0.00	100.00
160.0-161.0	0.0	0.0	20242.5	0.00	100.00
161.0-162.0	0.0	0.0	20242.5	0.00	100.00
162.0-163.0	0.0	0.0	20242.5	0.00	100.00
163.0-164.0	0.0	0.0	20242.5	0.00	100.00
164.0-165.0	0.0	0.0	20242.5	0.00	100.00
165.0-166.0	0.0	0.0	20242.5	0.00	100.00
166.0-167.0	0.0	0.0	20242.5	0.00	100.00
167.0-168.0	0.0	0.0	20242.5	0.00	100.00
168.0-169.0	0.0	0.0	20242.5	0.00	100.00
169.0-170.0	0.0	0.0	20242.5	0.00	100.00
170.0-171.0	0.0	0.0	20242.5	0.00	100.00
171.0-172.0	0.0	0.0	20242.5	0.00	100.00
172.0-173.0	0.0	0.0	20242.5	0.00	100.00
173.0-174.0	0.0	0.0	20242.5	0.00	100.00
174.0-175.0	0.0	0.0	20242.5	0.00	100.00
175.0-176.0	0.0	0.0	20242.5	0.00	100.00
176.0-177.0	0.0	0.0	20242.5	0.00	100.00
177.0-178.0	0.0	0.0	20242.5	0.00	100.00
178.0-179.0	0.0	0.0	20242.5	0.00	100.00
179.0-180.0	0.0	0.0	20242.5	0.00	100.00

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 5)

cone flux(90°): 15082.55 lm

%lum = 74.5%

%lamp = 74.5%

cone flux(120°): 18772.65 lm

%lum = 92.7%

%lamp = 92.7%

PPID Data Table

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G2.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G3.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G7.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G8.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G9.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G10.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G11.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G12.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G13.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G14.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G15.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G17.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G18.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G19.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G20.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G21.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G22.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G23.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G24.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G26.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G27.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G28.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G29.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G30.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G31.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G33.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G34.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G35.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G36.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 1)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G37.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G38.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G39.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G41.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G43.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G44.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 2)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G74.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G76.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G77.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G78.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G81.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G82.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G83.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G84.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G86.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G88.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G89.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G91.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G92.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G93.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G94.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G95.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G96.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G97.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G98.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G99.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G100.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G101.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G102.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G103.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G104.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G105.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G106.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G107.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G108.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G109.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G110.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 3)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G111.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G112.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G113.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G114.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G115.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G116.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G117.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G118.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G119.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G120.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G121.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G122.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G123.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G124.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G125.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G126.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G127.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G128.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G129.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G130.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G131.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G132.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G133.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G134.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G135.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G136.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G137.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G138.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G139.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G140.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G141.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G142.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G143.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G144.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G145.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G146.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G147.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 4)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G148.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G149.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G150.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G151.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G152.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G153.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G154.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G155.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G156.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G157.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G158.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G159.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G160.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G161.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G162.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G163.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G164.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G165.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G166.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G167.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G168.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G169.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G170.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G171.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G172.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G173.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G174.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G175.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G176.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G177.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G178.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G179.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G180.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 5)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G2.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G3.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G7.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G8.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G9.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G10.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G11.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G12.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G13.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G14.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G15.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G17.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G18.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G19.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G20.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G21.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G22.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G23.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G24.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G26.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G27.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G28.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G29.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G30.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G31.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G33.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G34.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G35.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G36.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 6)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G37.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G38.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G39.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G41.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G43.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G44.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 7)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G74.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G76.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G77.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G78.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G81.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G82.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G83.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G84.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G86.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G88.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G89.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G91.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G92.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G93.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G94.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G95.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G96.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G97.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G98.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G99.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G100.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G101.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G102.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G103.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G104.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G105.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G106.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G107.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G108.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G109.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G110.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 8)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G111.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G112.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G113.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G114.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G115.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G116.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G117.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G118.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G119.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G120.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G121.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G122.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G123.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G124.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G125.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G126.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G127.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G128.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G129.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G130.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G131.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G132.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G133.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G134.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G135.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G136.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G137.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G138.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G139.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G140.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G141.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G142.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G143.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G144.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G145.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G146.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G147.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 9)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G148.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G149.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G150.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G151.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G152.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G153.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G154.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G155.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G156.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G157.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G158.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G159.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G160.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G161.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G162.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G163.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G164.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G165.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G166.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G167.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G168.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G169.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G170.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G171.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G172.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G173.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G174.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G175.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G176.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G177.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G178.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G179.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G180.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 24.6 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

LED Average Luminance Report

Avg.L	cd/m ²
L 0-180(65) av	1.#J
L 0-180(75) av	1.#J
L 0-180(85) av	1.#J
L 90-270(65) av	1.#J
L 90-270(75) av	1.#J
L 90-270(85) av	1.#J
L 45(65) av	1.#J
L 45(75) av	1.#J
L 45(85) av	1.#J

Standard: GB/T 29293-2012