

Report No.:

Test Time: 2025/1/9 10:35

Luminaire Property

Luminaire Manufacturer:

Luminaire Category:

Lamp Catalog:

Number of Lamps:

Luminous Length (mm):

Luminous Height (mm):

Current: 0.663 A

Power Factor: 0.990

Luminaire Description:

Lamp Description:

Lumens per Lamp:

Luminous Width (mm):

Voltage: 120.0 V

Power: 78.80 W

Photometric Results

IES Classification: Type I

Total Rated Lamp Lumens: 11215.6 lm

Efficiency: 100%

Upward Ratio: 0%

C0r0 Intensity: 11662.85 cd

Pos of Max. Intensity: H270 V3

Beam Angle(C0/C180,C90/C270,C45/C225,C135/315): 54.6, 55.3, 54.4, 56.6

Longitudinal Classification: Very Short


Measurement Flux: 11215.6 lm

Downward Ratio: 100%


Luminaire Efficacy Rating (LER): 142.38

Max. Intensity: 11723.21 cd

Picture Of Luminaire



Luminous Intensity Distribution Curve



Unit: cd

Average Diffuse Angle(50%): 55.0°

— C0-C180 — C90-C270

C Plane (°):0.0-360.0: 22.5

Test Lab:

Test Type: TYPE C

Temperature: 25.1 'C

Operator:

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-3000

Distance: 14.631 m [K=1.0000]

Humidity:

Inspector:


Photon Intensity Distribution Curve



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Luminous Intensity Distribution Curve(cd/klm)



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:


Coefficients Of Utilization - Zonal Cavity Method

RC	0.8	0.8	0.8	0.8	0.7	0.7	0.7	0.7	0.5	0.5	0.5	0.3	0.3	0.3	0.1	0.1	0.1	0
RW	0.7	0.5	0.3	0.1	0.7	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0.5	0.3	0.1	0
RCR	RF = 0.2																	
0	1.19	1.19	1.19	1.19	1.16	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1	1.12	1.09	1.06	1.04	1.10	1.07	1.04	1.02	1.03	1.01	0.99	0.99	0.98	0.96	0.96	0.94	0.93	0.91
2	1.06	1.00	0.95	0.91	1.03	0.98	0.94	0.90	0.95	0.91	0.88	0.92	0.89	0.87	0.89	0.87	0.85	0.83
3	1.00	0.92	0.86	0.82	0.97	0.91	0.85	0.81	0.88	0.83	0.80	0.85	0.82	0.79	0.83	0.80	0.77	0.76
4	0.94	0.85	0.79	0.74	0.92	0.84	0.78	0.74	0.82	0.77	0.73	0.80	0.75	0.72	0.78	0.74	0.71	0.69
5	0.88	0.79	0.72	0.68	0.87	0.78	0.72	0.67	0.76	0.71	0.67	0.74	0.70	0.66	0.73	0.69	0.65	0.64
6	0.84	0.74	0.67	0.62	0.82	0.73	0.66	0.62	0.71	0.66	0.61	0.70	0.65	0.61	0.68	0.64	0.61	0.59
7	0.79	0.69	0.62	0.57	0.78	0.68	0.62	0.57	0.67	0.61	0.57	0.66	0.60	0.57	0.64	0.60	0.56	0.55
8	0.75	0.65	0.58	0.53	0.74	0.64	0.58	0.53	0.63	0.57	0.53	0.62	0.57	0.53	0.61	0.56	0.53	0.51
9	0.71	0.61	0.54	0.50	0.70	0.60	0.54	0.50	0.59	0.54	0.50	0.58	0.53	0.49	0.57	0.53	0.49	0.48
10	0.68	0.57	0.51	0.47	0.67	0.57	0.51	0.47	0.56	0.50	0.47	0.55	0.50	0.46	0.54	0.50	0.46	0.45

Spacing Criteria (0-180): 0.85

Spacing Criteria (90-270): 0.87

Spacing Criteria (Diagonal): 0.85



C Plane (°):0.0-360.0: 22.5

Test Lab:

Test Type: TYPE C

Temperature: 25.1 'C

Operator:

Gamma Plane (°):0.0-180.0:1.0


Test Device: GPM-3000

Distance: 14.631 m [K=1.0000]

Humidity:

Inspector:


Isocandela (rectangle)



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Isocandela (sphere)



Imax (100%): 11723 cd

(10%): 1172 cd
(25%): 2931 cd
(63%): 7386 cd

(16%): 1876 cd
(40%): 4689 cd
(100%): 11723 cd


CIE: narrow - short
CIE: Full-cut-off luminaire
Max.At90: 0.000 cd/klm

IES: Cut-off
Max.At80: 0.000 cd/klm
Max.80-90: 0.000 cd/klm

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

IsoLux Plot




Mounting Height: 10.0m		Max Lux(100%): 117.0 lx	
— (1%):	1.2 lx	— (2%):	2.3 lx
— (3%):	3.5 lx	— (4%):	4.7 lx
— (5%):	5.8 lx	— (6%):	7.0 lx
— (7%):	8.2 lx	— (8%):	9.4 lx
— (9%):	10.5 lx	— (10%):	11.7 lx

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Roadway CU Curve

Efficiency(%)





C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Lum Limit Curve

Dazzle	Quality	Illuminance (lx)							
1.15	A	2000	1000	500	<=300				
1.50	B		2000	1000	500	<=300			
1.85	C			2000	1000	500	<=300		
2.20	D				2000	1000	500	<=300	
2.55	E					2000	1000	500	<=300

a b c d e f g h




L(cd/sq.m)	G45	G50	G55	G60	G65	G70	G75	G80	G85
C0	1358	1112	976	858	716	564	319	153	29
C90	1142	927	744	535	338	171	60	24	13
C180	1245	1031	891	734	597	383	203	62	11
C270	1274	998	777	569	382	249	130	52	19

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:


Illuminance at a Distance



C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Vertical IsoLux Plot



Lowest(m): 1.0m Highest(m): 10.0m Max Lux: 11662.8 lx	
(1%): 116.6 lx	(2%): 233.3 lx
(3%): 349.9 lx	(4%): 466.5 lx
(5%): 583.1 lx	(6%): 699.8 lx
(7%): 816.4 lx	(8%): 933.0 lx
(9%): 1049.7 lx	(10%): 1166.3 lx

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

Area Flux Table


Unit: lm

Vertical plane		-90	-80	-70	-60	-50	-40	-30	-20	-10	0	10	20	30	40	50	60	70	80	90
Flux(E)	Flux(T)	0.0	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	0.5	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	13.3	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	59.7	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	128.8	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	228.7	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	468.8	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	899.7	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	2161.0	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	4997.3	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	3994.8	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	6440.0	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	064.7	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	509.1	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	1251.3	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	3147.3	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	77.0	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	22.8	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	1.7	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	11213	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0
0.0	9529	0.0	0.1	0.2	0.3	0.4	0.5	0.6	0.7	0.7	0.7	0.7	0.6	0.6	0.5	0.3	0.2	0.1	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:


The Average Illuminance Effective Figure



C Plane (°): 0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°): 0.0-180.0: 1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

FLUX DISTRIBUTION TABLE BASED ON THE IESNA LUMINAIRE CLASSIFICATION SYSTEM




ZONE	LUMENS	% LAMP LUMENS
FORWARD LIGHT	5496	49.0
FL (0°-30°)	3397	30.3
FM (30°-60°)	1796	16.0
FH (60°-80°)	291	2.6
FVH (80°-90°)	11	0.1
BACK LIGHT	5720	51.0
BL (0°-30°)	3538	31.5
BM (30°-60°)	1849	16.5
BH (60°-80°)	319	2.8
BVH (80°-90°)	14	0.1
UP LIGHT	0	0.0
UL (90°-100°)	0	0.0
UH (100°-180°)	0	0.0
TRAPPED LIGHT	NA	NA

BUG(Backlight,Uplight,Glare) Rating Base On TM-15-11	
Asymmetrical Luminaire Types (Type I,II,III,IV)	B4 U0 G1
Quadrilateral Symmetrical Luminaire Types (Type V,Area Light)	B4 U0 G1

C Plane (°):0.0-360.0: 22.5
Test Lab:
Test Type: TYPE C
Temperature: 25.1 'C
Operator:

Gamma Plane (°):0.0-180.0:1.0
Test Device: GPM-3000
Distance: 14.631 m [K=1.0000]
Humidity:
Inspector:

LCS Graph



Back Light

Forward Light

Scale= MAX LCS%

Trapped Light:NA,NA

Utilisation Factor Table(Floor cavity)

Utilisation Factors UF(F)			SHR NOM = 0.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.75	0.83	0.89	0.93	0.98	1.01	1.04	1.07	1.09	
	0.30		0.70	0.78	0.84	0.88	0.94	0.98	1.00	1.04	1.06	
	0.20		0.65	0.74	0.80	0.84	0.90	0.94	0.98	1.02	1.04	
0.50	0.50	0.20	0.74	0.82	0.87	0.90	0.95	0.98	1.00	1.03	1.05	
	0.30		0.69	0.77	0.82	0.86	0.92	0.95	0.98	1.01	1.03	
	0.20		0.65	0.73	0.79	0.83	0.89	0.92	0.95	0.99	1.01	
0.30	0.50	0.20	0.73	0.80	0.85	0.88	0.92	0.95	0.97	0.99	1.01	
	0.30		0.68	0.76	0.81	0.85	0.89	0.93	0.95	0.98	0.99	
	0.20		0.65	0.72	0.78	0.82	0.87	0.90	0.93	0.96	0.98	
0.00	0.00	0.00	0.63	0.70	0.75	0.79	0.84	0.87	0.89	0.92	0.93	
Rating:79W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Wall)

Utilisation Factors UF(W)			SHR NOM = 0.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.72	0.59	0.49	0.42	0.33	0.27	0.23	0.18	0.14	
	0.30		0.60	0.50	0.43	0.37	0.30	0.25	0.21	0.17	0.14	
	0.20		0.52	0.44	0.38	0.34	0.27	0.23	0.20	0.16	0.13	
0.50	0.50	0.20	0.69	0.56	0.47	0.40	0.31	0.29	0.22	0.17	0.13	
	0.30		0.59	0.48	0.41	0.36	0.29	0.24	0.20	0.16	0.13	
	0.20		0.51	0.43	0.37	0.32	0.26	0.22	0.19	0.15	0.12	
0.30	0.50	0.20	0.67	0.53	0.44	0.38	0.29	0.24	0.20	0.15	0.13	
	0.30		0.57	0.47	0.40	0.34	0.27	0.22	0.19	0.15	0.12	
	0.20		0.50	0.42	0.36	0.31	0.25	0.21	0.18	0.14	0.12	
0.00	0.00	0.00	0.38	0.30	0.25	0.22	0.17	0.14	0.12	0.09	0.07	
Rating:79W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Utilisation Factor Table(Ceiling cavity)

Utilisation Factors UF(C)			SHR NOM = 0.75									
Room Reflectance			Room Index(RI)									
Ceiling	Wall	Floor	0.75	1.00	1.25	1.50	2.00	2.50	3.00	4.00	5.00	
0.70	0.50	0.20	0.14	0.15	0.17	0.17	0.18	0.19	0.20	0.21	0.21	
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.19	0.19	
	0.20		0.05	0.07	0.09	0.10	0.12	0.14	0.15	0.17	0.18	
0.50	0.50	0.20	0.14	0.15	0.16	0.17	0.18	0.18	0.19	0.20	0.20	
	0.30		0.09	0.11	0.12	0.13	0.15	0.16	0.17	0.18	0.19	
	0.20		0.05	0.07	0.09	0.10	0.12	0.14	0.15	0.16	0.17	
0.30	0.50	0.20	0.13	0.14	0.15	0.16	0.17	0.18	0.18	0.19	0.19	
	0.30		0.09	0.10	0.12	0.13	0.14	0.15	0.16	0.17	0.18	
	0.20		0.05	0.07	0.09	0.10	0.12	0.13	0.14	0.16	0.17	
0.00	0.00	0.00	NA	NA	NA	NA	NA	NA	NA	NA	NA	
Rating:79W Photometrically tested without ceiling board. Multiply UF values by service correction factors Calculate in accordance with CIBSE Technical Memorandum NO.5 1980												

Zonal Lumen

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
0.0-1.0	11659.9	11.2	11.2	0.10	0.10
1.0-2.0	11646.1	33.4	44.6	0.30	0.40
2.0-3.0	11615.5	55.6	100.1	0.50	0.89
3.0-4.0	11569.2	77.5	177.6	0.69	1.58
4.0-5.0	11507.9	99.0	276.6	0.88	2.47
5.0-6.0	11428.4	120.1	396.7	1.07	3.54
6.0-7.0	11329.9	140.6	537.4	1.25	4.79
7.0-8.0	11215.8	160.5	697.9	1.43	6.22
8.0-9.0	11087.7	179.7	877.6	1.60	7.83
9.0-10.0	10943.4	198.1	1075.7	1.77	9.59
10.0-11.0	10783.2	215.5	1291.2	1.92	11.51
11.0-12.0	10608.7	231.9	1523.1	2.07	13.58
12.0-13.0	10419.4	247.3	1770.4	2.21	15.79
13.0-14.0	10216.6	261.5	2032.0	2.33	18.12
14.0-15.0	10003.7	274.7	2306.7	2.45	20.57
15.0-16.0	9778.9	286.6	2593.2	2.56	23.12
16.0-17.0	9537.0	297.0	2890.3	2.65	25.77
17.0-18.0	9283.6	306.1	3196.4	2.73	28.50
18.0-19.0	9016.3	313.7	3510.1	2.80	31.30
19.0-20.0	8728.7	319.5	3829.6	2.85	34.15
20.0-21.0	8426.1	323.6	4153.2	2.89	37.03
21.0-22.0	8107.2	325.8	4479.1	2.91	39.94
22.0-23.0	7768.1	326.0	4805.1	2.91	42.84
23.0-24.0	7413.5	324.2	5129.2	2.89	45.73
24.0-25.0	7048.0	320.5	5449.8	2.86	48.59
25.0-26.0	6671.5	315.0	5764.7	2.81	51.40
26.0-27.0	6287.1	307.6	6072.3	2.74	54.14
27.0-28.0	5900.5	298.8	6371.1	2.66	56.81
28.0-29.0	5510.0	288.3	6659.4	2.57	59.38
29.0-30.0	5115.0	276.2	6935.6	2.46	61.84
30.0-31.0	4723.4	262.9	7198.5	2.34	64.18
31.0-32.0	4337.8	248.5	7447.1	2.22	66.40
32.0-33.0	3957.7	233.2	7680.3	2.08	68.48
33.0-34.0	3590.8	217.3	7897.6	1.94	70.42
34.0-35.0	3240.9	201.3	8098.9	1.79	72.21
35.0-36.0	2912.4	185.5	8284.4	1.65	73.86

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 1)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
36.0-37.0	2614.0	170.5	8454.9	1.52	75.38
37.0-38.0	2346.4	156.6	8611.5	1.40	76.78
38.0-39.0	2109.5	144.0	8755.5	1.28	78.07
39.0-40.0	1905.7	132.9	8888.4	1.19	79.25
40.0-41.0	1734.0	123.5	9011.9	1.10	80.35
41.0-42.0	1588.7	115.4	9127.4	1.03	81.38
42.0-43.0	1466.3	108.6	9236.0	0.97	82.35
43.0-44.0	1364.1	103.0	9339.0	0.92	83.27
44.0-45.0	1277.4	98.2	9437.1	0.88	84.14
45.0-46.0	1203.9	94.2	9531.3	0.84	84.98
46.0-47.0	1140.9	90.8	9622.1	0.81	85.79
47.0-48.0	1085.3	87.7	9709.8	0.78	86.57
48.0-49.0	1035.3	85.0	9794.8	0.76	87.33
49.0-50.0	990.1	82.6	9877.4	0.74	88.07
50.0-51.0	947.8	80.2	9957.6	0.72	88.78
51.0-52.0	908.3	77.9	10035.5	0.70	89.48
52.0-53.0	871.0	75.8	10111.3	0.68	90.15
53.0-54.0	835.3	73.6	10185.0	0.66	90.81
54.0-55.0	801.3	71.5	10256.5	0.64	91.45
55.0-56.0	767.5	69.4	10325.9	0.62	92.07
56.0-57.0	734.9	67.2	10393.1	0.60	92.67
57.0-58.0	701.6	64.9	10457.9	0.58	93.24
58.0-59.0	667.1	62.4	10520.3	0.56	93.80
59.0-60.0	633.3	59.8	10580.2	0.53	94.33
60.0-61.0	599.3	57.2	10637.4	0.51	94.84
61.0-62.0	565.0	54.5	10691.8	0.49	95.33
62.0-63.0	532.0	51.7	10743.6	0.46	95.79
63.0-64.0	499.7	49.0	10792.6	0.44	96.23
64.0-65.0	467.0	46.2	10838.8	0.41	96.64
65.0-66.0	434.8	43.4	10882.2	0.39	97.03
66.0-67.0	402.9	40.5	10922.7	0.36	97.39
67.0-68.0	369.5	37.4	10960.2	0.33	97.72
68.0-69.0	335.7	34.2	10994.4	0.31	98.03
69.0-70.0	303.0	31.1	11025.5	0.28	98.31
70.0-71.0	271.4	28.1	11053.6	0.25	98.56
71.0-72.0	241.2	25.1	11078.7	0.22	98.78

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 2)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
72.0-73.0	212.9	22.3	11100.9	0.20	98.98
73.0-74.0	186.2	19.6	11120.5	0.17	99.15
74.0-75.0	160.5	17.0	11137.5	0.15	99.30
75.0-76.0	137.5	14.6	11152.1	0.13	99.43
76.0-77.0	116.7	12.4	11164.5	0.11	99.54
77.0-78.0	98.1	10.5	11175.0	0.09	99.64
78.0-79.0	80.8	8.7	11183.7	0.08	99.72
79.0-80.0	64.5	7.0	11190.6	0.06	99.78
80.0-81.0	50.8	5.5	11196.1	0.05	99.83
81.0-82.0	39.4	4.3	11200.4	0.04	99.86
82.0-83.0	31.1	3.4	11203.8	0.03	99.89
83.0-84.0	24.6	2.7	11206.5	0.02	99.92
84.0-85.0	19.6	2.1	11208.6	0.02	99.94
85.0-86.0	16.4	1.8	11210.4	0.02	99.95
86.0-87.0	14.4	1.6	11212.0	0.01	99.97
87.0-88.0	13.4	1.5	11213.5	0.01	99.98
88.0-89.0	13.0	1.4	11214.9	0.01	99.99
89.0-90.0	6.4	0.7	11215.6	0.01	100.00
90.0-91.0	0.0	0.0	11215.6	0.00	100.00
91.0-92.0	0.0	0.0	11215.6	0.00	100.00
92.0-93.0	0.0	0.0	11215.6	0.00	100.00
93.0-94.0	0.0	0.0	11215.6	0.00	100.00
94.0-95.0	0.0	0.0	11215.6	0.00	100.00
95.0-96.0	0.0	0.0	11215.6	0.00	100.00
96.0-97.0	0.0	0.0	11215.6	0.00	100.00
97.0-98.0	0.0	0.0	11215.6	0.00	100.00
98.0-99.0	0.0	0.0	11215.6	0.00	100.00
99.0-100.0	0.0	0.0	11215.6	0.00	100.00
100.0-101.0	0.0	0.0	11215.6	0.00	100.00
101.0-102.0	0.0	0.0	11215.6	0.00	100.00
102.0-103.0	0.0	0.0	11215.6	0.00	100.00
103.0-104.0	0.0	0.0	11215.6	0.00	100.00
104.0-105.0	0.0	0.0	11215.6	0.00	100.00
105.0-106.0	0.0	0.0	11215.6	0.00	100.00
106.0-107.0	0.0	0.0	11215.6	0.00	100.00
107.0-108.0	0.0	0.0	11215.6	0.00	100.00

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 3)

Gamma [°]	I _{mean} [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
108.0-109.0	0.0	0.0	11215.6	0.00	100.00
109.0-110.0	0.0	0.0	11215.6	0.00	100.00
110.0-111.0	0.0	0.0	11215.6	0.00	100.00
111.0-112.0	0.0	0.0	11215.6	0.00	100.00
112.0-113.0	0.0	0.0	11215.6	0.00	100.00
113.0-114.0	0.0	0.0	11215.6	0.00	100.00
114.0-115.0	0.0	0.0	11215.6	0.00	100.00
115.0-116.0	0.0	0.0	11215.6	0.00	100.00
116.0-117.0	0.0	0.0	11215.6	0.00	100.00
117.0-118.0	0.0	0.0	11215.6	0.00	100.00
118.0-119.0	0.0	0.0	11215.6	0.00	100.00
119.0-120.0	0.0	0.0	11215.6	0.00	100.00
120.0-121.0	0.0	0.0	11215.6	0.00	100.00
121.0-122.0	0.0	0.0	11215.6	0.00	100.00
122.0-123.0	0.0	0.0	11215.6	0.00	100.00
123.0-124.0	0.0	0.0	11215.6	0.00	100.00
124.0-125.0	0.0	0.0	11215.6	0.00	100.00
125.0-126.0	0.0	0.0	11215.6	0.00	100.00
126.0-127.0	0.0	0.0	11215.6	0.00	100.00
127.0-128.0	0.0	0.0	11215.6	0.00	100.00
128.0-129.0	0.0	0.0	11215.6	0.00	100.00
129.0-130.0	0.0	0.0	11215.6	0.00	100.00
130.0-131.0	0.0	0.0	11215.6	0.00	100.00
131.0-132.0	0.0	0.0	11215.6	0.00	100.00
132.0-133.0	0.0	0.0	11215.6	0.00	100.00
133.0-134.0	0.0	0.0	11215.6	0.00	100.00
134.0-135.0	0.0	0.0	11215.6	0.00	100.00
135.0-136.0	0.0	0.0	11215.6	0.00	100.00
136.0-137.0	0.0	0.0	11215.6	0.00	100.00
137.0-138.0	0.0	0.0	11215.6	0.00	100.00
138.0-139.0	0.0	0.0	11215.6	0.00	100.00
139.0-140.0	0.0	0.0	11215.6	0.00	100.00
140.0-141.0	0.0	0.0	11215.6	0.00	100.00
141.0-142.0	0.0	0.0	11215.6	0.00	100.00
142.0-143.0	0.0	0.0	11215.6	0.00	100.00
143.0-144.0	0.0	0.0	11215.6	0.00	100.00

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 4)

Gamma [°]	Imean [cd]	Zonal Flux [lm]	Sum Zonal Flux [lm]	Rel Zonal Flux [%]	Sum Rel Zonal Flux [%]
144.0-145.0	0.0	0.0	11215.6	0.00	100.00
145.0-146.0	0.0	0.0	11215.6	0.00	100.00
146.0-147.0	0.0	0.0	11215.6	0.00	100.00
147.0-148.0	0.0	0.0	11215.6	0.00	100.00
148.0-149.0	0.0	0.0	11215.6	0.00	100.00
149.0-150.0	0.0	0.0	11215.6	0.00	100.00
150.0-151.0	0.0	0.0	11215.6	0.00	100.00
151.0-152.0	0.0	0.0	11215.6	0.00	100.00
152.0-153.0	0.0	0.0	11215.6	0.00	100.00
153.0-154.0	0.0	0.0	11215.6	0.00	100.00
154.0-155.0	0.0	0.0	11215.6	0.00	100.00
155.0-156.0	0.0	0.0	11215.6	0.00	100.00
156.0-157.0	0.0	0.0	11215.6	0.00	100.00
157.0-158.0	0.0	0.0	11215.6	0.00	100.00
158.0-159.0	0.0	0.0	11215.6	0.00	100.00
159.0-160.0	0.0	0.0	11215.6	0.00	100.00
160.0-161.0	0.0	0.0	11215.6	0.00	100.00
161.0-162.0	0.0	0.0	11215.6	0.00	100.00
162.0-163.0	0.0	0.0	11215.6	0.00	100.00
163.0-164.0	0.0	0.0	11215.6	0.00	100.00
164.0-165.0	0.0	0.0	11215.6	0.00	100.00
165.0-166.0	0.0	0.0	11215.6	0.00	100.00
166.0-167.0	0.0	0.0	11215.6	0.00	100.00
167.0-168.0	0.0	0.0	11215.6	0.00	100.00
168.0-169.0	0.0	0.0	11215.6	0.00	100.00
169.0-170.0	0.0	0.0	11215.6	0.00	100.00
170.0-171.0	0.0	0.0	11215.6	0.00	100.00
171.0-172.0	0.0	0.0	11215.6	0.00	100.00
172.0-173.0	0.0	0.0	11215.6	0.00	100.00
173.0-174.0	0.0	0.0	11215.6	0.00	100.00
174.0-175.0	0.0	0.0	11215.6	0.00	100.00
175.0-176.0	0.0	0.0	11215.6	0.00	100.00
176.0-177.0	0.0	0.0	11215.6	0.00	100.00
177.0-178.0	0.0	0.0	11215.6	0.00	100.00
178.0-179.0	0.0	0.0	11215.6	0.00	100.00
179.0-180.0	0.0	0.0	11215.6	0.00	100.00

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

Zonal Lumen (Continue 5)

cone flux(90°): 9437.14 lm

%lum = 84.1%

%lamp = 84.1%

cone flux(120°): 10580.16 lm

%lum = 94.3%

%lamp = 94.3%

PPID Data Table

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G2.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G3.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G7.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G8.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G9.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G10.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G11.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G12.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G13.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G14.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G15.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G17.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G18.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G19.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G20.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G21.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G22.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G23.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G24.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G26.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G27.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G28.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G29.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G30.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G31.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G33.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G34.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G35.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G36.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 1)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G37.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G38.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G39.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G41.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G43.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G44.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 2)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G74.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G76.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G77.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G78.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G81.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G82.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G83.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G84.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G86.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G88.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G89.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G91.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G92.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G93.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G94.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G95.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G96.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G97.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G98.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G99.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G100.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G101.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G102.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G103.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G104.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G105.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G106.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G107.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G108.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G109.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G110.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 3)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G111.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G112.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G113.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G114.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G115.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G116.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G117.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G118.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G119.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G120.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G121.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G122.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G123.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G124.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G125.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G126.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G127.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G128.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G129.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G130.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G131.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G132.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G133.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G134.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G135.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G136.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G137.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G138.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G139.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G140.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G141.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G142.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G143.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G144.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G145.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G146.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G147.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 4)

Unit: cd

G\C	C0.0	C22.5	C45.0	C67.5	C90.0	C112.5	C135.0	C157.5	C180.0	C202.5
G148.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G149.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G150.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G151.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G152.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G153.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G154.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G155.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G156.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G157.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G158.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G159.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G160.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G161.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G162.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G163.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G164.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G165.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G166.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G167.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G168.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G169.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G170.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G171.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G172.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G173.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G174.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G175.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G176.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G177.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G178.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G179.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
G180.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 5)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G1.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G2.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G3.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G4.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G5.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G6.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G7.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G8.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G9.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G10.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G11.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G12.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G13.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G14.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G15.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G16.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G17.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G18.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G19.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G20.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G21.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G22.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G23.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G24.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G25.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G26.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G27.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G28.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G29.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G30.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G31.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G32.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G33.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G34.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G35.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G36.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 6)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G37.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G38.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G39.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G40.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G41.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G42.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G43.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G44.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G45.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G46.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G47.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G48.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G49.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G50.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G51.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G52.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G53.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G54.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G55.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G56.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G57.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G58.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G59.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G60.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G61.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G62.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G63.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G64.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G65.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G66.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G67.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G68.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G69.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G70.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G71.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G72.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G73.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 7)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G74.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G75.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G76.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G77.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G78.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G79.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G80.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G81.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G82.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G83.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G84.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G85.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G86.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G87.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G88.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G89.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G90.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G91.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G92.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G93.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G94.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G95.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G96.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G97.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G98.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G99.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G100.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G101.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G102.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G103.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G104.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G105.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G106.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G107.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G108.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G109.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G110.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 8)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G111.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G112.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G113.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G114.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G115.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G116.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G117.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G118.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G119.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G120.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G121.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G122.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G123.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G124.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G125.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G126.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G127.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G128.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G129.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G130.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G131.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G132.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G133.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G134.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G135.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G136.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G137.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G138.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G139.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G140.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G141.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G142.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G143.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G144.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G145.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G146.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G147.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

PPID Data Table (Continue 9)

Unit: cd

G\C	C225.0	C247.5	C270.0	C292.5	C315.0	C337.5	C360.0			
G148.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G149.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G150.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G151.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G152.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G153.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G154.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G155.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G156.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G157.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G158.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G159.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G160.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G161.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G162.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G163.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G164.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G165.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G166.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G167.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G168.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G169.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G170.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G171.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G172.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G173.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G174.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G175.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G176.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G177.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G178.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G179.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			
G180.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0			

C Plane (°):0.0-360.0: 22.5
 Test Lab:
 Test Type: TYPE C
 Temperature: 25.1 'C
 Operator:

Gamma Plane (°):0.0-180.0:1.0
 Test Device: GPM-3000
 Distance: 14.631 m [K=1.0000]
 Humidity:
 Inspector:

LED Average Luminance Report

Avg.L	cd/m ²
L 0-180(65) av	1.#J
L 0-180(75) av	1.#J
L 0-180(85) av	1.#J
L 90-270(65) av	1.#J
L 90-270(75) av	1.#J
L 90-270(85) av	1.#J
L 45(65) av	1.#J
L 45(75) av	1.#J
L 45(85) av	1.#J

Standard: GB/T 29293-2012