

Date:	Project:	Type:	Notes:	Catalog #:
-------	----------	-------	--------	------------

L5600-AOK 150LPW SERIES Adjustable LED Wrap Fixtures

The L5600-AOK LED Wrap is a functional multi-purpose wraparound with four wattage and five CCT options with 150 LPW efficiency. Perfect for any back of house applications.



Features & Specifications

Applications

Ideal for use in warehouses, distribution centers, garages, utility rooms, corridors, schools, offices, hospitals and canopies.

Construction

Steel sheet housing with Frosted PMMA lens. Long lasting white finish for high durability.

Mounting

Surface mount (standard). Suspension mounting available.

Electrical

Utilizes high-efficiency LED power supply and circuit boards. 120-277V & 0-10V dimming standard. 50/60HZ input frequency. Sensor enabled with 12V Aux Connection plus Standard purple & pink dimming wires.

Operating Temperature

Suitable for -20°C (-4F) – 50°C (122F) Ambient

CRI

80+

Lumen Maintenance

L70 rating of 100,000 hours

Warranty

Five-year warranty. Terms and Conditions Apply. See warranty documentation for more information.

Certification

UL Damp Listed. Adheres to LM79, LM80 and TM21 industry standards.



Performance Data

FSC Part #	Form Factor	Rated Wattage	Kelvin Temp	Delivered Lumens	CCT
L5624-3000L-7-AOK (DLC 6.0 - S-ZVD0H5)	2FT 7 Inch	10	3000	1600	160
		10	3500	1600	160
		10	4000	1600	160
		10	5000	1600	160
		10	6500	1600	160
		13	3000	2000	154
		13	3500	2000	154
		13	4000	2000	154
		13	5000	2000	154
		13	6500	2000	154
		17	3000	2600	153
		17	3500	2600	153
		17	4000	2600	153
		17	5000	2600	153
		17	6500	2600	153
		20	3000	3000	150
		20	3500	3000	150
		20	4000	3000	150
		20	5000	3000	150
		20	6500	3000	150
L5648-6000L-7-AOK (DLC 6.0 - S-WPF8VX)	4FT 7 inch	21	3000	3200	152
		21	3500	3200	152
		21	4000	3200	152
		21	5000	3200	152
		21	6500	3200	152
		26	3000	4000	154
		26	3500	4000	154
		26	4000	4000	154
		26	5000	4000	154
		26	6500	4000	154
		34	3000	5100	150
		34	3500	5100	150
		34	4000	5100	150
		34	5000	5100	150
		34	6500	5100	150
		40	3000	6000	150
		40	3500	6000	150
		40	4000	6000	150
		40	5000	6000	150
		40	6500	6000	150

FSC Part #	Form Factor	Rated Wattage	Kelvin Temp	Delivered Lumens	CCT
L5648-6000L-9-AOK (DLC 6.0 - S-WPF8VX)	4FT 9 Inch	21	3000	3200	152
		21	3500	3200	152
		21	4000	3200	152
		21	5000	3200	152
		21	6500	3200	152
		26	3000	4000	154
		26	3500	4000	154
		26	4000	4000	154
		26	5000	4000	154
		26	6500	4000	154
		34	3000	5100	150
		34	3500	5100	150
		34	4000	5100	150
		34	5000	5100	150
		34	6500	5100	150
		40	3000	6000	150
		40	3500	6000	150
		40	4000	6000	150
		40	5000	6000	150
		40	6500	6000	150

Catalog Ordering

Sample Part # L5648-6000L-7-AOK

L56								
1	2	3	4	5	5	5	5	5

1 - Series

2 - Length in Inches/Lumens/ Width

3 - Type

L56

24 - 3000L-7 (2 Foot, 10W, 7")
(2 Foot, 13W, 7")
(2 Foot, 17W, 7")
(2 Foot, 20W, 7")

48 - 6000L-7 (4 Foot, 21W, 7")
(4 Foot, 26W, 7")
(4 Foot, 34W, 7")
(4 Foot, 40W, 7")

48 - 6000L-9 (4 Foot, 21W, 9")
(4 Foot, 26W, 9")
(4 Foot, 34W, 9")
(4 Foot, 40W, 9")

AOK (Adjustable Output and Kelvin Temp 30K, 35K, 40K, 50K & 65K)

4- Controls

OS On / Off PIR Occupancy Sensor

PRGOS-LS Sensorswitch LSXR Occ Sensor w/ Dimming Photocell

PRGOS-LR IRTEC LRD Programmable Occ Sensor w/ Remote Control

5 - Accessories

EM10WT20 Title 20 Compliant Emergency Battery Backup, 10 Watts, ~1300 Lumens
(lumens will change based on fixture selection)

ETS-DR UL924 Emergency Lighting Control Device

PLG 6' SJT Cord & Plug

Physical Characteristics

Dimensions

Version	Depth	Length	Width	Weight
2FT	2.8"	24.5"	7.1"	6lbs
4FT	2.8"	47.7"	7.1"	8lbs
4FT	2.8"	47.7"	9.4"	9lbs

