

|       |          |       |        |            |
|-------|----------|-------|--------|------------|
| Date: | Project: | Type: | Notes: | Catalog #: |
|-------|----------|-------|--------|------------|

## L5600-AOK SERIES Adjustable LED Wrap Fixtures

The L5600-AOK LED Wrap is a functional multi-purpose wraparound with four wattage and five CCT options with 150 LPW efficiency. Perfect for any back of house applications.



### Features & Specifications

#### Applications

Ideal for use in warehouses, distribution centers, garages, utility rooms, corridors, schools, offices, hospitals and canopies.

#### Construction

Steel sheet housing with Frosted PMMA lens. Long lasting white finish for high durability.

#### Mounting

Surface mount (standard). Suspension mounting available.

#### Electrical

Utilizes high-efficiency LED power supply and circuit boards. 120-277V & 0-10V dimming standard. 50/60HZ input frequency. Sensor enabled with 12V Aux Connection plus Standard purple & pink dimming wires.

#### Operating Temperature

Suitable for -20°C (-4F) – 50°C (122F) Ambient

#### CRI

80+

#### Lumen Maintenance

L70 rating of 100,000 hours

#### Warranty

Five-year warranty. Terms and Conditions Apply. See warranty documentation for more information.

#### Certification



## Performance Data

| FSC Part #        | Form Factor | Rated Wattage | Kelvin Temp | Delivered Lumens | CCT |
|-------------------|-------------|---------------|-------------|------------------|-----|
| L5624-3000L-7-AOK | 2FT         | 10            | 2700        | 1600             | 160 |
|                   |             | 10            | 3000        | 1600             | 160 |
|                   |             | 10            | 3500        | 1600             | 160 |
|                   |             | 10            | 4000        | 1600             | 160 |
|                   |             | 10            | 5000        | 1600             | 160 |
|                   |             | 13            | 2700        | 2000             | 154 |
|                   |             | 13            | 3000        | 2000             | 154 |
|                   |             | 13            | 3500        | 2000             | 154 |
|                   |             | 13            | 4000        | 2000             | 154 |
|                   |             | 13            | 5000        | 2000             | 154 |
|                   | 7 Inch      | 17            | 2700        | 2600             | 153 |
|                   |             | 17            | 3000        | 2600             | 153 |
|                   |             | 17            | 3500        | 2600             | 153 |
|                   |             | 17            | 4000        | 2600             | 153 |
|                   |             | 17            | 5000        | 2600             | 153 |
|                   |             | 20            | 2700        | 3000             | 150 |
|                   |             | 20            | 3000        | 3000             | 150 |
|                   |             | 20            | 3500        | 3000             | 150 |
|                   |             | 20            | 4000        | 3000             | 150 |
|                   |             | 20            | 5000        | 3000             | 150 |
| L5648-6000L-7-AOK | 4FT         | 21            | 2700        | 3200             | 152 |
|                   |             | 21            | 3000        | 3200             | 152 |
|                   |             | 21            | 3500        | 3200             | 152 |
|                   |             | 21            | 4000        | 3200             | 152 |
|                   |             | 21            | 5000        | 3200             | 152 |
|                   |             | 26            | 2700        | 4000             | 154 |
|                   |             | 26            | 3000        | 4000             | 154 |
|                   |             | 26            | 3500        | 4000             | 154 |
|                   |             | 26            | 4000        | 4000             | 154 |
|                   |             | 26            | 5000        | 4000             | 154 |
|                   | 7 inch      | 34            | 2700        | 5100             | 150 |
|                   |             | 34            | 3000        | 5100             | 150 |
|                   |             | 34            | 3500        | 5100             | 150 |
|                   |             | 34            | 4000        | 5100             | 150 |
|                   |             | 34            | 5000        | 5100             | 150 |
|                   |             | 40            | 2700        | 6000             | 150 |
|                   |             | 40            | 3000        | 6000             | 150 |
|                   |             | 40            | 3500        | 6000             | 150 |
|                   |             | 40            | 4000        | 6000             | 150 |
|                   |             | 40            | 5000        | 6000             | 150 |

| FSC Part #        | Form Factor | Rated Wattage | Kelvin Temp | Delivered Lumens | CCT |
|-------------------|-------------|---------------|-------------|------------------|-----|
| L5648-6000L-9-AOK | 4FT         | 21            | 2700        | 3200             | 152 |
|                   |             | 21            | 3000        | 3200             | 152 |
|                   |             | 21            | 3500        | 3200             | 152 |
|                   |             | 21            | 4000        | 3200             | 152 |
|                   |             | 21            | 5000        | 3200             | 152 |
|                   |             | 26            | 2700        | 4000             | 154 |
|                   |             | 26            | 3000        | 4000             | 154 |
|                   |             | 26            | 3500        | 4000             | 154 |
|                   |             | 26            | 4000        | 4000             | 154 |
|                   |             | 26            | 5000        | 4000             | 154 |
|                   | 9 Inch      | 34            | 2700        | 5100             | 150 |
|                   |             | 34            | 3000        | 5100             | 150 |
|                   |             | 34            | 3500        | 5100             | 150 |
|                   |             | 34            | 4000        | 5100             | 150 |
|                   |             | 34            | 5000        | 5100             | 150 |
|                   |             | 40            | 2700        | 6000             | 150 |
|                   |             | 40            | 3000        | 6000             | 150 |
|                   |             | 40            | 3500        | 6000             | 150 |
|                   |             | 40            | 4000        | 6000             | 150 |
|                   |             | 40            | 5000        | 6000             | 150 |

|            |   |   |   |   |   |   |   |   |
|------------|---|---|---|---|---|---|---|---|
| <b>L56</b> |   |   |   |   |   |   |   |   |
| 1          | 2 | 3 | 4 | 5 | 5 | 5 | 5 | 5 |

**1 - Series**

**2 - Length in Inches/Lumens/ Width**

**3 - Type**

**L56**

**24 - 3000L-7** (2 Foot, 10W, 7")  
(2 Foot, 13W, 7")  
(2 Foot, 17W, 7")  
(2 Foot, 20W, 7")

**48 - 6000L-7** (4 Foot, 21W, 7")  
(4 Foot, 26W, 7")  
(4 Foot, 34W, 7")  
(4 Foot, 40W, 7")

**48 - 6000L-9** (4 Foot, 21W, 9")  
(4 Foot, 26W, 9")  
(4 Foot, 34W, 9")  
(4 Foot, 40W, 9")

**AOK** (Adjustable Output and Kelvin Temp 27K, 30K, 35K, 40K & 50K)

**4- Controls**

**5 - Accessories**

**OS** On / Off PIR Occupancy Sensor  
**PRGOS-LS** Sensorswitch LSXR Occ Sensor w/ Dimming Photocell  
**PRGOS-LR** IRTEC LRD Programmable Occ Sensor w/ Remote Control

**EM10WT20** Title 20 Compliant Emergency Battery Backup, 10 Watts, ~1300 Lumens (lumens will change based on fixture selection)  
**ETS-DR** UL924 Emergency Lighting Control Device  
**PLG 6'** SJT Cord & Plug

## Physical Characteristics

### Dimensions

| Version | Depth | Length | Width | Weight |
|---------|-------|--------|-------|--------|
| 2FT     | 2.8"  | 24.5"  | 7.1"  | 6lbs   |
| 4FT     | 2.8"  | 47.7"  | 7.1"  | 8lbs   |
| 4FT     | 2.8"  | 47.7"  | 9.4"  | 9lbs   |

